



Philippine
Overseas
Employment
Administration

Republic of the Philippines
Department of Labor and Employment
BFO Building, Ortigas Avenue cor. EDSA, Mandaluyong City 1501
Website: www.poea.gov.ph E-mail: info@poea.gov.ph
Hotlines: 722-1144, 722-1155



REQUEST FOR PRICE QUOTATION

03 July 2018

SUPPLY OF PUBLIC ADDRESS AUDIO SYSTEM FOR GROUND FLOOR LOBBY POEA CENTRAL (RFQ 60R-2018)

Date: _____
Name of Company: _____
Address: _____
Business Permit No. _____
TIN No. _____
PhilGEPS Registration No.: _____

Please quote your lowest net price, taxes included for the item/s described below and submit your **signed and sealed** quotation to the POEA BAC Secretariat, BFO Building, Ortigas Ave., cor Edsa, Mandaluyong City not later than 2p.m. on **09 July 2018** at which date and time, all submitted quotations will be opened. Late bids shall not be received.

Available fund is ONE HUNDRED TWENTY NINE THOUSAND PESOS (**₱129,000.00**).

CANDIDA B. VISTRO
Vice-Chairperson
Bids and Awards Committee

After having carefully read and accepted the Terms and Conditions, I/we submit our quotation/s for the item/s as follows:

QTY./ UNIT	DESCRIPTION	UNIT PRICE	TOTAL PRICE
1 Lot	Supply of Public Address Audio System for Ground Floor Lobby POEA Central Office Power Amplifier (2 units) Features: Two Channel, 450Watts per Channel @4 ohms, 330watts per Channel @8 ohms Stereo/Parallel/Bridge-mono mode Efficient forced-air cooling prevents excessive thermal buildup Electronically balanced RCA & XLR inputs; binding post and Speakon ® outputs Fault for each channel Two level controls, power switch power LED and Six LEDs which indicates signal presence. Protection against shorts, no-load, on/off thumps and radio-frequency interference Specification:	₱ _____	₱ _____

1. Frequency Response: 20 Hz - 20 kHz, +0/-1 dB (at 1 watt)
THD: <0.5%, 20 Hz - 20 kHz
2. Intermodulation Distortion: =/ <0.35% (60 Hz and 7 kHz at 4:1 from full rated output to -30 dB)
3. Slew Rate: >10V/us
4. Voltage Gain: 31 dB
5. Damping Factor: (8 ohms, 10 Hz to 400 Hz) >200
6. Signal To Noise Ratio (A-weighted): >100 dB
7. Crosstalk (below rated power) 20 Hz to 1 kHz: -75 dB, -59 dB
8. Input Sensitivity: (for full rated power at 8 ohms) 0.775V or 1.4V
9. Input Impedance (nominal balanced, unbalanced): 20kΩ, 10kΩ
10. AC Line Voltage and Frequency Configurations Available: (+10%) 120V~60 Hz; 220V~50/60 Hz; 230-240V~50/60 Hz
11. Dimensions: 19" x 3.5" x 12.4" (48.3cm x 8.9cm x 31.5cm)
12. Weight: 28lbs (12.7kg)
13. IEC Power Connector: 15A

Mixing Console (Audio Mixer) (1 unit)

Features:

1. Total inputs 12 mono+2 stereo 2 configurable auxiliary buses
2. XLR-type and ¼" metal jack connector sockets
3. RCA phono stereo playback inputs and record outputs
4. 3-band EQ with a swept mid on mono input
5. 2-band EQ on stereo inputs
6. TRS insert sockets and inserts on all mono inputs and mix output
7. Ten-segment LED output metering
8. Intuitive and comprehensive solo system
9. Headphone output
10. Easily rack mountable

15" 2-Way Loud Speaker System (2pair)

Specification:

Power Rating	250 W / 1000W
Frequency Range (-10 dB)	41Hz - 18kHz
Frequency Response (±3 dB)	59Hz -13kHz
Sensitivity (@1m)	99 dB SPL (1w/1m)
Nominal Impedance	8 ohms
Recommended Amplifier Power	250 W to 500 W into 8 ohms
Maximum SPL	129 dB
Nominal Dispersion	90° x 50°
Crossover Frequency	2.2 kHz
Dimensions (H x W x D)	699 mm x 460 mm x 432 mm (27.5 in x 18.1 in x 17 in)
Weight	27.4 kg (60.5 lb)

High Frequency Driver	2414H-C , 1" exit compression driver mounted on Progressive Transition™ Waveguide		
Low Frequency Driver	M115-8A		
Input Connectors	Neutrik® Speakon® NL-4 (x1); .25in TS phone jack (x1); parallel		
Movable Rack, Cables and Connectors (1 lot)			
Name of Company			
Complete Address			
Telephone No./Fax			
Printed Name of Owner/Authorized Representative and Signature			

TERMS AND CONDITIONS:

1. Bidders shall provide correct and accurate information required in this form.
2. Price quotation/s must be valid for a period of *Thirty (30) calendar days* from the date of submission.
3. Price quotation/s, to be denominated in Philippine peso shall include all taxes, duties and/or levies payable.
4. Quotations exceeding the Approved Budget for the Contract shall be rejected.
5. Award of contract shall be made to the lowest quotation which complies with the minimum technical specifications
6. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by your or any of your duly authorized representative/s.
7. The POEA shall have the right to inspect and/or to test the goods to confirm their conformity to the technical specifications.
8. Liquidated damages equivalent to one tenth of one percent (0.001%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. The POEA may rescind or terminate the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies available under circumstances.
9. The bidder shall submit the following requirements:
 - a) Business Permit/Mayor's Permit;
 - b) PhilGEPS Registration;
 - c) Omnibus Sworn Statement.